



Model: CMRTSG500

500L Glass Door RTS Cabinet

Overview

- +15°C to +25°C temperature range
- Core temperature display, represents your vaccine vial through **iCOOL** INTELLIGENT COOLING temperature probe
- External digital controller and temperature display
- Battery back up
- Annual service & Calibration available
- Fitted lock with 2 keys



1 YEAR PARTS & LABOUR WARRANTY

ANNUAL SERVICE & CALIBRATION AVAILABLE

Key Features



Controller

Controller system. Read, record, reset with the touch of one button. Adjustable temperature setting.



Battery back up

Battery back up should there ever be a power outage the battery backup will continue to monitor the internal temperature of the fridge.



Porthole

Factory fitted porthole enables quick and easy access for any secondary temperature monitoring probes.



LED lighting

Low voltage LED lighting improves running cost as no heat is produced. Long lasting.



Flexible storage

Multiple shelf locations. Back stop on every shelf provides a flexible storage solution.

Details

Model: CMRTSG500

| | |
|---|--|
| Gross Capacity (litres) | 495 |
| Net Capacity (litres) | 480 |
| Unit External Width (mm) | 1180 |
| Unit External Depth (mm) | 600 |
| Unit External Height (mm) | 1530 |
| Product Weight (kg) | 121 |
| Packed Width (mm) | 1230 |
| Packed Depth (mm) | 650 |
| Packed Height (mm) | 1700 |
| Packed Weight (kg) | 132 |
| Temperature Range | +15°C to +25°C |
| External Finish, Internal Finish | Painted Steel, Painted Steel |
| Battery Back Up | Yes |
| Door Finish, Door Type, Door Style | Painted Steel, Glass, Hinged, Right Hand |
| Open Door Sensor | Yes |
| Lock | 2 Locks, 4 Keys |
| Adjustable Feet (number) | Lockable Castors (4) |
| Porthole | Yes |
| Porthole Location | Rear, Middle |
| Temperature Display on Panel, Temperature Alarm, Remote Alarm Contacts, Audible Alarms, Visual Alarms | Yes |

| | |
|-----------------------------------|-------------------------|
| Number of Shelves | 8 (6 full size, 2 base) |
| Number of Shelf Positions | 10+ |
| Shelf Material | Plastic Coated Wire |
| Interior Light | Yes |
| Light Type | LED |
| Light Activation | Switch |
| Fan | Yes |
| Spark Free | No |
| Controller Type | Digital, External |
| Number of Probes | 2 |
| Probe Type | Air & Load |
| Ambient Temperature Range | +10°C to +30°C |
| Refrigerant Type | R600a |
| CFC Free, HCFC Free, Ammonia Free | Yes |
| Voltage Supply | 220-240V/ 50Hz |
| Certification | CE/UK |
| Noise Level (dBA) | 50 |
| Input Power (W) | 380 |
| Cable Length (cm) | 20 |
| Energy Consumption (kWh/annum) | 3.9 |

Related Products



CMRTSS500
500L Solid Door
RTS Cabinet



CMDL01
Advanced Data Logger
with LCD Display



COMBI01
Keyless
Combination Lock