

Model: CMRTSG500

500L Glass Door RTS Cabinet

Overview

- +15°C to +25°C temperature range
- Core temperature display, represents your vaccine vial through **iCOOL** temperature probe
- External digital controller and temperature display
- Battery Back up
- Annual service & Calibration available
- Fitted lock with 2 keys



5 YEARS PARTS & LABOUR WARRANTY

ANNUAL SERVICE & CALIBRATION AVAILABLE

Key Features



Controller

Controller system. Read, record, reset with the touch of one button. Adjustable temperature setting.



Battery

Backup should there ever be a power outage the battery backup will continue to monitor the internal temperature of the freezer.



Porthole

Factory fitted porthole enables quick and easy access for any secondary temperature monitoring probes.



LED Lighting

Low voltage LED lighting improves running cost as no heat is produced. Long lasting.



Flexible storage

Multiple shelf locations. Back stop on every shelf provides a flexible storage solution.

Details

Model: CMRTSG500

Gross Capacity (litres)	495
Net Capacity (litres)	480
Unit External Width (mm)	1180
Unit External Depth (mm)	609
Unit External Height (mm)	1530
Product Weight (kg)	130
Packed Width (mm)	1230
Packed Depth (mm)	655
Packed Height (mm)	1710
Packed Weight (Kg)	142
Temperature Range	+15°C to +25°C
External Finish, Internal Finish	Painted Steel, Painted Steel
Battery Back Up	Yes
Door Finish, Door Type, Door Style	Painted Steel, Glass, Hinged, Right Hand
Open Door Sensor	Yes
Lock	2 Locks, 4 Keys
Adjustable Feet (number)	4 Lockable Castors
Porthole	Yes
Porthole Location	Rear, Middle
Temperature Display on Panel, Temp Alarm, Remote Alarm Contacts, Audible Alarms, Visual Alarms	Yes

Number of Shelves	8 (6 full size, 2 base)
Number of Shelf Positions	10+
Shelf Material	Plastic Coated Wire
Interior Light	Yes
Light Type	LED
Light Activation	Switch
Fan	Yes
Spark Free	No
Controller Type	Digital, External
Number of Probes	2
Probe Type	Air & Load
Ambient Temperature Range	+10°C to +30°C
Refrigerment Type	R600a
CFC Free, HCFC Free, Ammonia Free	Yes
Voltage Supply	220-240V/ 50Hz
Certification	CE/UK
Noise Level (dba)	50
Input Power (W)	380
Cable Length (Cm)	20
Energy Consumption (KWh/annum)	3.9

Related Products

**CMRTSS500**500L Solid Door
RTS Cabinet**CMDL01**Advanced Data Logger
with LCD Display**COMBI01**Keyless
Combination Lock