

Model: CMS500

500L Large Solid Door Refrigerator

Overview

- +2°C to +8°C temperature range
- Core temperature display, represents your vaccine vial through **iCOOL** temperature probe
- External digital controller and temperature display
- Battery Back up
- Annual service & Calibration available
- Fitted lock with 2 keys


5 YEARS PARTS & LABOUR WARRANTY
ANNUAL SERVICE & CALIBRATION AVAILABLE

Key Features



Controller

Easy-to-use control system with a one-touch button to read, record, and reset settings. Includes fully adjustable temperature controls for precise monitoring.



Battery back up

In the event of a power outage, the integrated battery backup ensures continuous monitoring of the internal temperature—keeping your contents safe and secure.



Porthole

Pre-fitted factory porthole allows simple, hassle-free access for adding secondary temperature monitoring probes.



LED lighting

Energy-efficient, low-voltage LED lighting reduces running costs and eliminates excess heat. Durable and long-lasting for everyday use.



Flexible storage

Customise your space with multiple shelf positions. Each shelf includes a back stop to prevent items from being pushed too far—practical and versatile.

Details

Model: CMS500

Gross Capacity (litres)	495	Number of Shelves	8 (6 full size, 2 base shelf)
Net Capacity (litres)	480	Number of Shelf Positioins	10+
Unit External Width (mm)	1180	Shelf Material	Plastic Coated Wire
Unit External Depth (mm)	600	Interior Light	Yes
Unit External Height (mm)	1530	Light Type	LED
Product Weight (kg)	108	Light Activation	Switch
Packed Width (mm)	1230	Fan	Yes
Packed Depth (mm)	650	Spark Free	No
Packed Height (mm)	1700	Controller Type	Digital, External
Packed Weight (kg)	119	Number of Probes	2
Temperature Range	+2°C to +8°C	Probe Type	Air & Load
External Finish, Internal Finish	Painted Steel, Painted Steel	Ambient Temperature Range	+10°C to +30°C
Battery Back Up	No	Refrigerment Type	R600a
Door Finish, Door Type, Door Style	Painted Steel, Solid, Hinged, Right Hand	CFC Free, HCFC Free, Ammonia Free	Yes
Open Door Sensor	Yes	Voltage Supply	220-240V/ 50Hz
Lock	2 Locks, 4 Keys	Certification	CE/UK
Adjustable Feet (number)	Lockable Castors (4)	Noise Level (dBa)	50
Porthole	Yes	Input Power (W)	380
Porthole Location	Rear, Middle	Cable Length (Cm)	20
Temperature Display on Panel, Temperature Alarm, Remote Alarm Contacts, Audible Alarms, Visual Alarms	Yes	Energy Consumption (KWh/annum)	3.9

Related Products



CMG500

Large Glass Door Refrigerator



CMDL01

Advanced Data Logger with LCD Display



COMBI01

Keyless Combination Lock